

## **AMENDMENTS TO THE CLAIMS**

This listing of claims will replace all prior versions, and listings, of claims in the application:

### **Listing of Claims:**

- 1           1. (Currently amended) A method for checkpointing an application,  
2    comprising:  
3           dynamically linking an interceptor library into the application during a  
4    run-time invocation of the application, wherein the run-time invocation occurs  
5    after the application has been compiled and linked, and wherein the interceptor  
6    library is dynamically linked by simply setting an environment variable, without  
7    having to perform an entire static linking process;  
8           intercepting a function call produced by the application at the interceptor  
9    library;  
10          recording parameters of the function call to create a checkpoint that  
11    includes information about the function call parameters;  
12          making the function call by referring to function pointers saved within the  
13    interceptor library;  
14          receiving results of the function call; and  
15          forwarding results of the function call back to the application.
  
- 1           2. (Original) The method of claim 1, further comprising creating a  
2    checkpoint by:  
3           stopping the application;  
4           retrieving the recorded parameters;

5           saving the checkpoint data, including the recorded parameters, to  
6   secondary storage; and  
7           resuming the application.

1           3. (Original) The method of claim 2, further comprising using the  
2   checkpoint to restore the application.

1           4. (Original) The method of claim 2, wherein saving the checkpoint data to  
2   secondary storage involves saving the checkpoint data to a persistent storage.

1           5. (Original) The method of claim 2, wherein saving the checkpoint data to  
2   secondary storage involves saving the checkpoint data in a file system, or a  
3   database.

1           6. (Original) The method of claim 1, wherein making the function call  
2   involves referencing the function through a function pointer.

1           7. (Original) The method of claim 1, further comprising recording the  
2   results of the function call to facilitate creating a checkpoint that includes  
3   information about the results of the function call.

1           8. (Original) The method of claim 1, wherein the function calls can include  
2   system calls or lib calls.

1           9. (Original) The method of claim 1, wherein the parameters can include:  
2   file paths;  
3   thread flags; and  
4   timer-thread relationships.

1           10. (Currently amended) A computer-readable storage medium storing  
2 instructions that when executed by a computer cause the computer to perform a  
3 method for checkpointing an application, the method comprising:  
4           dynamically linking an interceptor library into the application during a  
5 run-time invocation of the application, wherein the run-time invocation occurs  
6 after the application has been compiled and linked, and wherein the interceptor  
7 library is dynamically linked by simply setting an environment variable, without  
8 having to perform an entire static linking process;  
9           intercepting a function call produced by the application at the interceptor  
10 library;  
11           recording parameters of the function call to create a checkpoint that  
12 includes information about the function call parameters;  
13           making the function call by referring to function pointers saved within the  
14 interceptor library;  
15           receiving results of the function call; and  
16           forwarding results of the function call back to the application.

1           11. (Original) The computer-readable storage medium of claim 10, further  
2 comprising creating a checkpoint by:  
3           stopping the application;  
4           retrieving the recorded parameters;  
5           saving the checkpoint data, including the recorded parameters, to  
6 secondary storage; and  
7           resuming the application.

1           12. (Original) The computer-readable storage medium of claim 11, further  
2 comprising using the checkpoint to restore the application.

1           13. (Original) The computer-readable storage medium of claim 11,  
2 wherein saving the checkpoint data to secondary storage involves saving the  
3 checkpoint data to a persistent storage.

1           14. (Previously presented) The computer-readable storage medium of  
2 claim 11, wherein saving the checkpoint data to secondary storage involves saving  
3 the checkpoint data in a file system, or a database.

1           15. (Original) The computer-readable storage medium of claim 10,  
2 wherein making the function call involves referencing the function through a  
3 function pointer.

1           16. (Original) The computer-readable storage medium of claim 10,  
2 wherein the method further comprises recording the results of the function call to  
3 facilitate creating a checkpoint that includes information about the results of the  
4 function call.

1           17. (Original) The computer-readable storage medium of claim 10,  
2 wherein the function calls can include system calls or lib calls.

1           18. (Original) The computer-readable storage medium of claim 10,  
2 wherein the parameters can include:  
3           file paths;  
4           thread flags; and  
5           timer-thread relationships.

1           19. (Currently amended) An apparatus that checkpoints an application,  
2 comprising:

3           a dynamic linking mechanism that is configured to dynamically link an  
4    interceptor library into the application during a run-time invocation of the  
5    application, wherein the run-time invocation occurs after the application has been  
6    compiled and linked, and wherein the interceptor library is dynamically linked by  
7    simply setting an environment variable, without having to perform an entire static  
8    linking process;

9           an intercepting mechanism within the interceptor library that is configured  
10   to intercept a function call produced by the application;

11          a recording mechanism that is configured to record parameters of the  
12   function call to facilitate creating a checkpoint that includes information about the  
13   function call parameters;

14          a calling mechanism that is configured to make the function call by  
15   referring to function pointers saved within the interceptor library;

16          a receiving mechanism that is configured to receive results of the function  
17   call; and

18          a forwarding mechanism that is configured to forward results of the  
19   function call back to the application.

1           20. (Original) The apparatus of claim 19, further comprising a checkpoint  
2   creation mechanism that is configured to:

3           stop the application;

4           retrieve the recorded parameters;

5           save the checkpoint data, including the recorded parameters, to secondary  
6   storage; and to

7           resume the application.

1           21. (Original) The apparatus of claim 20, further comprising a restoration  
2 mechanism that is configured to use the checkpoint data to restore the application  
3 to the checkpointed state.

1           22. (Original) The apparatus of claim 20, wherein the checkpoint creation  
2 mechanism is configured to save checkpoint data to a persistent storage.

1           23. (Original) The apparatus of claim 20, wherein the checkpoint creation  
2 mechanism is configured to save the checkpoint data in a file system, or a  
3 database.

1           24. (Original) The apparatus of claim 19, wherein the calling mechanism  
2 is configured to make the function call by referencing the function through a  
3 function pointer.

1           25. (Original) The apparatus of claim 19, further comprising a recording  
2 mechanism that is configured to record the results of the function call to facilitate  
3 creating a checkpoint that includes information about the results of the function  
4 call.

1           26. (Original) The apparatus of claim 19, wherein the function calls can  
2 include system calls or lib calls.

1           27. (Original) The apparatus of claim 19, wherein the parameters can  
2 include:  
3           file paths;  
4           thread flags; and  
5           timer-thread relationships.